



Hovermap ST

SPECIFICATIONS

A versatile SLAM-based mapper, making data capture fast, simple, and safe. Hovermap ST is a smart mobile scanning unit equally capable above ground or belowground, indoors or out. Its tough, lightweight, IP65 weather sealed design enables the capture of data in harsh, GPS-denied or hazardous environments.

MAPPING SPECIFICATIONS

SLAM mapping	Simultaneous Localization and Mapping (SLAM) based LiDAR mapping +/- 0.03% drift
LiDAR range	0.40 m to 100 m (1.3 to 330 ft)
LiDAR accuracy	+/- 30 mm (1 1/4 in)
Mapping accuracy	+/- 20 mm (3/4 in) in general environments +/- 15 mm (19/32 in) in typical underground and indoor environments +/- 5 mm (7/32 in) isolated change detection capability
Angular field of view	360° x 290°
LiDAR data acquisition speed	Single Return Mode: up to 300,000 points/sec Dual Return Mode: up to 600,000 points/sec
Maximum data capture traveling speed	Vehicle: 40 km/h (24.9 mph); flight: 5 m/s (16.4 fps) above ground, 2 m/s (6.6 fps) underground or confined spaces
Start / stop scanning while walking or hovering	Yes
Outputs	Full resolution point cloud, decimated point cloud, trajectory file
Point cloud file format	.las, .laz, .ply, .dxf, E57
Point cloud attributes	Intensity, range, time, return number (strongest & last) and ring number
Processing parameters	Pre-set profiles with 20+ adjustable parameters
USB3	High-speed data offload
Storage	512 Gigabytes – approximately 8 hours of sensor data
Operating temperature	-10 to 45° C (14 to 113° F)

PHYSICAL SPECIFICATIONS

IP Rating	IP65
Weight	1.6 kg (3.63 lb)
Input voltage	14 - 54V, powered from a battery or auxiliary power input
Deployment	Drone/UAV, handheld, backpack, vehicle, tether, ground robot
Supported drones	DJI M210v1, DJI M300, Acecore Zoe
Quick release mount	Yes
Auxiliary port	Proprietary connector
USB port	Yes
WiFi Antenna	Internal

AUTONOMY SPECIFICATIONS

Flight modes	Pilot Assist: Non-GPS flight, position hold, assisted flight, collision avoidance, regulated flight speed. Autonomous Waypoint Mode: Autonomous navigation to waypoints
AL2 waypoint types	2D, 3D, planar, height
AL2 navigation modes	Guided exploration, local and global path planning
Autopilot compatibility	DJI, ArduPilot (Acecore Zoe)
Omnidirectional collision avoidance	360° x 360°; size of an obstacle > 2 mm (3/32 in) wire; range 1.2 to 40 m (3.9 to 131 ft); In-flight adjustable safety distance

INCLUDED ACCESSORIES
 Handle, cables, case
 Universal mounting plate
 V-Mount 98Wh, 14.8v battery
 Standard battery charger
 Battery belt clip

OPTIONS AND ACCESSORIES
 Colorization kit;
 Vehicle mounts; Protective cage; Hard case backpack ; Automated Ground Control targets;
 Cavity Monitoring System adaptor kit; Battery fast charger kit